

S-86,761

RL-13,880

IL-10127

Express Mail No.: EM508979560US

SOL-GEL MANUFACTURED ENERGETIC MATERIALS

BY

Randall L. Simpson (USA)
1766 Sixth Street
Livermore, CA 94550

Ronald S. Lee (USA)
1822 Vancouver Way
Livermore, CA 94550

Thomas M. Tillotson (USA)
210 Berverdor
Tracy, CA 95376

Lawrence W. Hrubesh (USA)
19 Greyeagle Court
Pleasanton, CA 94566

Rosalind W. Swansiger (USA)
1446 Vancouver Way
Livermore, CA 94550

Glenn A. Fox (USA)
1818 Aquarius Street
Livermore, CA 94550

A PROCESS FOR PRODUCING ENERGETIC MATERIALS
SOL-GEL MANUFACTURED ENERGETIC MATERIALS

The United States Government has rights in this invention pursuant to Contract No. W-7405-ENG-48 between the United States Department of Energy and the University of California for the operation of Lawrence Livermore National Laboratory.

BACKGROUND OF THE INVENTION

The present invention relates to energetic materials, particularly to the manufacture of energetic materials, and more particularly to the manufacture of energetic materials using sol-gel chemistry.

Energetic materials are herein defined as any material which stores chemical energy in a fixed volume. Explosives, propellants, and pyrotechnics are examples of energetic materials. Reaction results from either shock or heat. Explosives and propellants may be thought of as a means of storing gas as a "solid". Pyrotechnics typically release much of their energy as heat.

Energetic materials consist of fuels and oxidizers which are intimately mixed. This is done by incorporating fuels and oxidizers within one molecule or through chemical and physical mixtures of separate fuel and oxidizer ingredients. The material may also contain other constituents such as binders, plasticizers, stabilizers, pigments, etc.

Traditional manufacturing of energetic materials involves processing granular solids into parts. These materials may be pressed or cast to shape. Performance properties are strongly dependent on particle size distribution, surface area of the constituents, and void volume. In many cases achieving fast energy release rates, as well as insensitivity to unintended initiation, necessitates the use of small particles ($\leq 100\mu\text{m}$) which are intimately mixed. Reproducibility in performance is adversely affected by the difficulties of synthesizing and processing materials with the same particle morphology. Manufacturing these granular substances into complex shapes is often difficult due to limitations in processing highly solid filled materials.

An example of an existing limitation of processing granular solids is in manufacturing energetic materials for detonators. The state-of-the-art now requires the precise synthesis and recrystallization of explosive powders. These powders typically have high surface areas (e.g., $>1\text{m}^2/\text{g}$). The powders are weighed and compacted at high pressures to make pellets. Handling fine grain powders is very difficult. Dimensional and mechanical tolerances may be very poor as the pellets may contain no binder. Changes in the density and dimensions of the pellets affect both initiation and detonation properties. Manufacturing rates are also low as the process is usually done one at a time. Certification of material is typically done by expensive, end-use detonation performance testing and not solely by chemical and physical characterization of the explosive powder. As these detonators or initiating explosives are sensitive, machining to shape pressed pellets is typically not done.

Another current limitation is producing precise intimate mixtures of fuels and oxidizers. The energy release rates of energetic materials are determined by the overall chemical reaction rate. Monomolecular energetic

materials have the highest power as the energy release rates are primarily determined by intramolecular reactions. However, energy densities can be significantly higher in composite energetic materials. Reaction rates (power) in these systems are typically controlled by mass transport diffusion rates.

5 The present invention solves many of these prior problems by manufacturing energetic materials through the use of sol-gel chemistry. Sol-gel chemistry is known in the art and broadly described here, but described hereinafter in greater detail to provide an understanding of this technology. In one approach, using sol-gel chemistry, a solution including explosive
10 materials is made. That solution is then gelled to form a cross-linked skeleton, which may be either inert, or reactive, or energetic, and a continuous liquid phase. The liquid phase is then extracted to produce either a xerogel or an aerogel. A solid so produced has high surface area and homogeneity. During the solution stage of the operation, the solution may be
15 easily cast into molds to produce final parts. By applying a stress during removal of the liquid phase, dense parts may be obtained. Alternately, explosive molding powders may be made which can be used as feedstock for pressing operations. The molding beads will have a high degree of uniformity in the microstructure. As these beads are orders of magnitude
20 larger than explosive powders used in traditional processing they may be easily handled. Also, through using sol-gel chemistry the intimacy of mixing can be dramatically improved over mixing granular solids. Numerous synthetic routes may be carried out utilizing sol-gel chemistry in the processing of energetic materials; these include solution addition,
25 powder/particle addition, nano-composites, and functionalized solid networks.

SUMMARY OF THE INVENTION

It is an object of the present invention to produce energetic materials using sol-gel chemistry.

5 A further object of the invention is to minimize prior problems associated with the manufacturing of energetic materials by the use of sol-gel processing.

A further object of the invention is to produce explosives using sol-gel chemistry which enables microstructural control of the explosive material to the nanometer scale.

10 Another object of the invention is to manufacture energetic materials using sol-gel chemistry, whereby the intimacy of mixing can be controlled and dramatically improved over the prior procedures of mixing granular solids or epitaxial deposition.

15 Another object of the invention is produced by sol-gel processing a solid skeleton composed of fuel with the oxidizer trapped within the pores, or vice versa.

Another object of the invention is to provide a process using sol-gel chemistry to create a material that has high energy, such as a strategic rocket propellant with high power, such as an ideal explosive.

20 Another object of the invention is to provide a process utilizing sol-gel chemistry wherein the sensitivity of the energetic materials can be readily controlled.

Another object of the invention is to utilize sol-gel chemistry in the processing of energetic materials by at least solution addition, powder/particle addition, nano-composites, and functionalized solid networks.

Another object of the invention is to utilize sol-gel chemistry for the preparation of energetic materials with improved homogeneity, and/or can be cast to near-net shapes, and/or can be made into precision molding powders.

5 Other objects and advantages of the present invention will become apparent from the following description and the accompanying drawings. Basically, the invention involves sol-gel manufactured energetic material and a process utilizing sol-gel chemistry for producing energetic materials. Energetic materials manufactured using sol-gel chemistry possess superior
10 properties in terms of microstructural homogeneity, and/or can be more easily processed and/or processed with greater precision and accuracy, than can be obtained by the prior known technology. The sol-gel manufactured energetic materials can be utilized as precision detonator explosives, precision explosives, propellants, pyrotechnics, and high power composites.

15 The sol-gel process is a synthetic chemical process where reactive monomers are mixed into a solution; polymerization occurs leading to a highly cross-linked three-dimensional solid network resulting in a gel. The composition, pore and primary particles sizes, gel time, surface areas, and density may be tailored and controlled by the solution chemistry. The gels are
20 then subjected to either supercritical extraction or controlled slow evaporation of the liquid phase from the gel. Supercritical extraction of these gels allows the surface tension of the leaving liquid phase to be reduced to near zero and results in a highly porous skeletal structure which is low density aerogel, while controlled slow evaporation of the liquid phase from
25 the gels leads to a xerogel, which may be high density. Applying stress during the extraction phase can result in high density materials. By use of the sol-gel

processing, energetic materials can be made, for example, by solution addition solution exchange, powder/particle addition, functionalized solid network, functionalized explosive network, and micron to submicron scale composite energetic materials.

5 The methodologies of the above six sol-gel manufacturing techniques are briefly described as follows:

10 Solution Addition: The energetic material constituent is dissolved in a solvent which is compatible with the reactive monomer and mixed into the pre-gel solution prior to gelation. Upon gelation, the energetic material constituent is uniformly distributed within the pores of the solid network formed by the polymerization of the reactive monomer.

Solution Exchange: After gelation, the liquid phase is exchanged with another liquid which contains an energetic material constituent, thus allowing deposition of the energetic material constituent within the gel.

15 Powder/Particle Addition: The energetic material constituent, in particulate form, is either mixed with the pre-gel solution or added to a pre-made gel, resulting in a composite of gel and suspended particles.

20 Functionalized Solid Network: Use of reactive monomers which have functionalized sites dangling throughout the solid network after gelation. Dissolution of the energetic material constituent in mutually compatible solvents and diffusing into the gel allows the energetic material constituent to react and bind to the functionalized site. Thus, the amount of energetic material constituent may be controlled by the number of functionalized sites while ensuring homogeneity at the molecular level.

25 Functionalized Energetic Network: Functionalizing the energetic material constituent molecules so that they can be reacted in solution to

directly form a three dimensional solid (gel) which incorporates the energetic molecules at the finest scale. In this embodiment, the solid network is the energetic material and, if desired, the concentration can be controlled by co-reacting with other inert reactive monomers.

5 Micron To Sub-Micron (Nano) Scale Composite Energetic Materials:

Higher performance energetic materials can be made in which the skeletal structure and the surrounding phase serve as fuels and oxidizers to form a composite energetic material. Conductive gels (e.g., carbon aerogels) may be used as substrates for the electrochemical precipitation of metal fuels, or
10 metals may be deposited within non-conductive aerogels via decomposition from the gas or liquid phase. Void space may then be used for the addition of an oxidizer and other energetic material constituents.

The sol-gel manufacturing of energetic materials solves many of the prior above-described problems associated with the manufacture of energetic
15 materials.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated into and form a part of the disclosure, illustrate embodiments of the invention and, together with the description, serve to explain the principles of the invention.

Figures 1A and 1B illustrate micro and nanoscale gel structures
20 produced by sol-gel processing.

Figure 2 illustrates the general process for sol-gel synthesis and processing.

Figures 3A-3D illustrate various embodiments in which an explosive (fuel/oxidizer) may be incorporated utilizing sol-gel processing in accordance with the present invention.

5 Figures 4A-4C illustrate low density energetic material made in accordance with the present invention which may serve as hydrodynamic working fluids.

Figure 5 illustrates multifunctional energetic monomers which can control the gel composition in producing energetic materials by sol-gel chemistry.

10 Figure 6 graphically illustrates high explosive detonation experiments utilizing an RDX xerogel made in accordance with the present invention.

DETAILED DESCRIPTION OF THE INVENTION

15 The present invention involves sol-gel manufactured energetic materials and a process for manufacturing the energetic material utilizing sol-gel chemistry. The manufacturing process of this invention solves many of the prior problems associated with the fabrication of energetic materials (explosives, propellants, and pyrotechnics). As pointed out above, energetic materials basically consist of fuel and oxidizers which are intimately mixed, but may also contain other constituents such as binders, plasticizers,
20 stabilizers, pigments, etc. The prior problems associated with mixing of the constituents and forming of these materials into desired shapes have been significantly reduced, if not eliminated, by utilizing sol-gel processing in accordance with the present invention.

Initiation and detonation properties are dramatically affected by the microstructural properties of the explosives. Explosives produced using sol-gel chemistry enable microstructural control to the nanometer scale. Possible applications include: mass production of precision detonator pellets, net shape casting of initiating explosives, optical surface initiation, detonation wave shaping, hydrodynamic fluids, initiation explosive trains, detonation cord, high-power-high-energy composite explosives, low energy density solid high explosives, and desensitization of explosives powders. Basic scientific elements include: initiation and detonation mechanisms in the nanometer range, mass transport and intramolecular reaction kinetics at high pressure and temperature, and sol-gel chemistry.

Sol-gel methodology produces high surface area, porous solids which may be cast to near-net shape. The microstructure, comprised of nanometer-sized pores and linked primary particles, as well as the elemental composition, can be tailored and controlled by solution chemistry. Figures 1A and 1B illustrate typical microscale and mesoscale gel structures, with Figure 1B being an enlargement of a cell of Figure 1. In Figure 1A, the arrow indicates the mesoporosity of the gel structures being $\sim 2 \leq d \leq 50$ nanometers, while the arrow in Figure 1B indicates the microporosity within a cell of the structure being $d \leq \sim$ nanometer, with (d) indicating molecular dimensions.

The general process for sol-gel synthesis and processing is illustrated in Figure 2. Monomers are reacted in solution to produce small nanometer size particles, a "sol", which cross-link to form a three-dimensional solid network with the remaining solution residing within open pores, a "gel". Controlled evaporation of the liquid phase in a gel results in a xerogel, while supercritical extraction eliminates the surface tension of the retreating liquid

phase, producing highly porous solids, aerogels. Silica aerogel, prepared by supercritically extracting tetramethoxysilane, is one example. Also, carbon aerogels having similar cell structures are produced using supercritical extraction to produce an aerogel or produce a xerogel using controlled evaporation. The gel may be energetic or non-energetic itself, depending on the composition of the solution (sol). Energetic materials may be held within the micro or mesoscale porosity. Solids may be directly added to the gels, and the type of solvent extraction will be determined by the desired composition of the end produce. As a general rule, aerogels have a substantially lower density and higher porosity than xerogels.

The methodology of the present invention solves many problems found in existing state-of-the-art energetic materials synthesis and processing. One example is the pressing of powders of energetic material for detonators and related devices. Low manufacturing rates, difficulty in handling fine powders, and the inability to produce precise geometric shapes may be solved by this approach. Another current experimental limitation is producing precise intimate mixtures of fuels and oxidizers. Using sol-gel chemistry, the intimacy of mixing can be controlled and dramatically improved over the current art of mixing granular solids or epitaxial deposition. A solid skeleton composed of the fuel with the oxidizer trapped within the pores, or vice versa, is envisioned. A material goal that has eluded conventional technology is to create a material that has the high energy of a strategic rocket propellant (roughly two times the energy density of a conventional high explosive) with the power of an ideal explosive.

Perhaps more importantly, however, the sol-gel technology may be able to make energetic materials which have entirely new and desirable

properties. A significant observation in a preliminary proof-of-principle experiment is that the presence of the gel structure dramatically decreased the impact sensitivity of an explosive. This result was counter to that expected. If generally true this one technical element could have a dramatic international impact in the handling and processing of explosive materials.

The desensitization of explosive powders as a consequence of gelation may hold true for shock loading as well as impact. A recent detonation experiment (see Figure 6) found that when an RDX-silica-based xerogel was shocked at pressures adequate to initiate the insensitive high explosive ultrafine TATB it failed to initiate. This is remarkable in that standard nitramine based explosives that have inert binder volumes similar to the RDX-silica xerogel tested are readily initiatable.

Increased dimensional control will also enable high quality experiments to be run where chemical and mass transport limited kinetics may be determined more accurately than by conventional approaches. The next generation detonation modeling will focus on chemical kinetics and species equilibration and rely on these data. The computational tools being developed in molecular dynamic and mesoscale simulations of hydrodynamics are commensurate with the nanometer scale dimensions in sol-gel based energetic materials. Thus, sol-gel chemistry offers microstructural control of an explosive matrix not attainable with physical mixing as well as the potential for low cost manufacturing methods not achievable with vapor deposition techniques.

Figures 3A-3D illustrate different approaches using sol-gel chemistry to produce energetic materials. As shown in Figure 3A, the gel may be explosive, while in Figure 3B crystallites in pores may be explosive,

while explosive powders may be added to the gel network, as shown in Figure 3C, or as shown in Figure 3D the structure may be an oxidizer or fuel, or the cell pores may contain a fuel or oxidizer.

As shown in Figure 4A, low density energetic materials may serve as hydrodynamic fluids. This may be accomplished by providing a low density structural support, that can gasify, such as an explosive aerogel as shown in Figure 4A which may be formulated using the sol-gel chemistry approach to provide an energetic gel as seen in Figure 4B, or a nanocrystalline structure containing the explosive as shown in Figure 4C. Activation of the explosive aerogel produces a fluid as indicated by the arrows in Figure 4A. Sol-gel chemistry provides for tailored and energetic staging fluids (e.g., soft launches).

Figure 5 illustrates multifunctional energetic monomers which can control gel composition, using traditional sol-gel monomers resorcinol and benzene-1,3-dithiol, or using energetic gas generators GAP, PGN, PNIMMO, BAMO, and LLM-101.

Figure 6 graphically illustrates the results of shock initiation experiments using RDX porous xerogel. The experiments illustrated the inability to initiate 33 wt.% RDX porous xerogel, and the ability to initiate 80 wt.% RDX porous xerogels.

As pointed out above, traditional manufacturing of energetic materials involves processing granular solids, and in the production of detonators, for example, powders of energetic material and a binder are typically mixed and compacted at high pressure to make pellets. Performance properties are strongly dependent on particle size distribution, surface area of its constituents, homogeneity of the mix, and void volume. By sol-gel

processing in accordance with the present invention, detonators can be produced with fast energy release rate and are insensitive to unintended initiation. The following sets forth the preparation of such detonators from xerogel molding powders and aerogels.

5 Sol-gel chemistry is known in the art for producing a variety of metal oxide, organic, and carbon aerogels and xerogels, and these materials have been utilized for various purposes. The composition of the aerogels or xerogels is varied by the sol-gel processing, whereby various surface areas, densities, etc. can be produced. These materials have found use in various
10 insulation applications including the recent Mars Pathfinder mission, electrochemical applications such as electrodes in ultra capacitors, molds for the casting of metals, and for the capture of cosmic dust. Thus, a detailed description of the sol-gel processing is not deemed necessary except for the application to the manufacture of energetic materials, and the above-
15 described general sol-gel processing technique is deemed sufficient. While numerous synthetic routes utilizing sol-gel processing of energetic materials, which include solution addition, solution exchange, powder/particle addition, functionalized solid network, functionalized explosive network, and micron to submicron scale composites (nano-composites), each briefly
20 described above, four of these processing approach have been thus far experimentally verified, and a detailed description of each is set forth, followed by a brief description of the characterization of these materials.

Solution Addition:

25 The idea is to crystallize the energetic material within the pores of a sol-gel derived solid. In practice, the energetic material is dissolved in a solvent which is compatible with the reactants and used for density control of

the resulting gel. Optimum composition for use as detonators would be approximately 90 wt.% energetic material/10 wt.% inert matrix. Due to the solubility limits of most energetic materials the preparation of low density porous solids are necessitated to meet this requirement. For this work, energetic molecules, hexahydro-1,3,5-trinitro-1,3,5-triazine (RDX) and 2,2-bis[(nitroxy)methyl]-1,3-propanediol,dinitrate (PETN), were crystallized within the pores of silica matrices.

Either single or two-step silicon alkoxide synthesis methodology described elsewhere [2,14,15] may be used to prepare the silica matrix. We found it necessary to prepare and mix three solutions in this synthesis to avoid unwanted precipitation of the energetic material. A 100% excess of water was added to promote the hydrolysis reactions. Either an acid or base catalyst may be used but for reasons discussed later fluoroboric acid is our catalyst of choice. A typical recipe would consist of: solution A-1.25g tetramethoxysilane (TMOS) + 1.00g acetone, solution B- 1.00g acetone + 0.60g water + 150 μ l fluoroboric acid, solution C- 6.00g acetone + .4000g RDX. Subsequential additions of solutions B and C are poured into a stirring solution A. This combined solution is stirred for a few minutes and poured into molds where gelation occurs in <24 hours. The mass weight of the silica matrix is controlled by the amount of alkoxide added to solution A, while the mass weight of RDX is limited to its solubility in acetone. Xerogeling was done at 25°C by poking pinholes in the polyethylene foil covering the mold held in place by rubber bands. Supercritical extraction (SCE) of the gels into aerogels was done by the low temperature CO₂ process. To prevent loss of the solubilized energetic molecule during SCE, the RDX or PETN was first crystallized within the pores of the matrix by replacing the pore liquor with a

solvent in which the energetic material is insoluble but one which is still miscible in CO₂. Ethanol was used for these experiments. The pore liquor was exchanged along with the crystallization of the energetic molecule by immersing the gel into large excesses of ethanol three times over 24 hours.

5 This extraction route was preferred to the high temperature autoclave process because most energetic molecules, like RDX and PETN, are extremely heat sensitive either degrading or detonating at temperatures >100°C.

Powder/Particle Addition:

10 Loading particles/powders uniformly inside gels is problematic because even ultrafine particles will tend to settle before the gel sets up, producing a non-uniform distribution. Also, particles will agglomerate in solution exacerbating this problem further. We describe here, for the first time, a methodology which we call the gel mending approach that dramatically improves the homogeneity of particle loaded monoliths.

15 Conceptually, it makes use of the observation that a monolithic gel can be regenerated from gel fragments. First, a gel is prepared. Then the gel is fractionated by any process that breaks the gel into small fragments, i.e., a blender. With continued mixing, the powder/particles are added until a uniform dispersion is reached. Gels made from metal alkoxides will self-

20 mend and reform a monolith including the dispersed powder/particles with the addition of a small amount of solvent. At this point, the gel can be dried by the above mentioned processes to produce xerogels and aerogels with a uniform distribution of the powder or particles.

25 For this work, we made silica gels from TMOS, dispersing either RDX or PETN, and reforming the gel with a small addition of methanol. The reformed gels were translucent to opaque depending on the wt.%

concentration of the energetic material. Xerogel molding powders were produced by the above described xerogeling process and pressed into pellets for drop hammer sensitivity and shock initiation experiments. One advantage of this approach over the solution addition approach is the ease of preparing highly concentrated energetic materials with precise wt.% ratio's.

Functionalized Solid Networks:

Building in functionalized reaction sites as part of the solid network is one way to disperse an energetic molecule on the molecular scale. Either the energetic molecule can bond directly with the functionalized site or another functional group can be bound to this site which in turn captures the energetic molecule. One idea of how this might work is to use reactive monomers which have functional sites that don't participate in the crosslinking reactions leading to the gel state. Dissolution of the energetic molecule in mutually compatible solvents and diffusing into the gel allows the energetic material to react and bind to that functionalized site. As such, the amount of energetic molecules may be controlled by the number of functionalized sites while ensuring homogeneity at the molecular level.

We have synthesized organic aerogels with thiol groups (-SH) distributed along the solid network by reacting 1,3-dithiol benzene with formaldehyde using a base catalyst. In order to get the 1,3 dithiol benzene into a water solution it was necessary to use the sodium salt. To do this, sodium was reacted with an excess of methanol to prepare sodium methoxide which upon the addition of 1,3 dithiol benzene forms as products the sodium salt and methanol. All reactions were carried out under nitrogen in a shrink line. The excess methanol is distilled off and the sodium salt added to a formaldehyde/water/catalyst solution to induce gelation. As in previous

organic synthesis with resorcinol, 2 moles of formaldehyde for each mole of the sodium salt is used, water as the diluent for density control, and sodium carbonate as a base catalyst. Gelation at 70°C was considerably longer than the R-F gels. A yellow transparent gel was exchanged with acetone prior to xerogeling or low temperature CO₂ SCE.

Nano-Composites:

Our invention of a nano-composite material is essentially a physical mixture of fuels and oxidizers at the molecular level. Energetic materials primary ingredients are oxidizers and fuels. Here, we use sol-gel technology to compose the solid skeleton out of a fuel while trapping the oxidizer within the pores or vice versa. One goal which has eluded conventional technology is to create a nano composite that has the energy of a rocket propellant along with the power of a high explosive. Through mixing at the molecular level, reaction rates can be dramatically increased using sol-gel chemistry.

Our early experimental work has been to prepare an organic skeleton to be used as the fuel with an oxidizer trapped in the meso-pores. The organic skeleton is synthesized from the polycondensation of resorcinol (1,3-dihydroxybenzene) with formaldehyde. The basic recipe is two moles of formaldehyde for every mole of resorcinol base, catalyzed with sodium carbonate. The oxidizer, ammonium perchlorate, is dissolved in water and is used as a diluent in the synthesis for density control. Gel times at 40°C for the resorcinol/catalyst ratio (R/C=50) used was approximately 2 days, which is considerably longer than the synthesis without ammonium perchlorate. The water was exchanged with methanol prior to xerogeling and with either methanol or ethylacetate prior to low temperature CO₂ SCE.

Characterization Methods:

Characterization of these materials is more difficult than typical sol-gel derived materials due to the energetic component of the matrices.

Differential scanning calorimetry (DSC) was used to determine if the energetic material was present in the final dried products. Optical, scanning and transmission electron microscopy were used to study the microstructure.

The drop hammer test, a standard energetic material characterization technique, was used to measure the impact sensitivity of our produced materials. In this test, a 2.5kg weight is dropped from a pre-set height onto a 35mg pressed pellet of material, and explosion or non-explosion is recorded. Depending on this outcome the hammer is raised or lowered, resulting in a series of drops with either explosion or non-explosion being recorded. The criterion for "explosion" is an arbitrary set level of sound produced by the explosive or impact. The tests were summarized as H50, the height in centimeters in which the probability of explosion is 50%.

The shock initiation experiments, see Figure 6, used to determine if these materials were detonable were done by the flyer-plate technique, another energetic material standard. In this technique, an explosive charge is ignited with the expanding gas pressure slamming into a metal foil sending a shock wave through a pressed pellet which is observed through a lithium fluoride crystal by a laser velocimeter.

The differential scanning calorimetry (DSC) analysis confirmed the presence of RDX and PETN in the sol-gel processed materials. PETN based materials had a small endotherm at 143°C followed by an exotherm at 200°C characteristic of neat PETN. Corresponding agreement with RDX was found with RDX based aerogels and xerogels.

Monolithic aerogels prepared by the solution addition of RDX showed that monolithicity was maintained in compositions up to 45 wt.% RDX in a 55 wt.% SiO₂ matrix.

5 The impact sensitivity of an energetic material to unintended initiation is an important safety factor in their use. The drop-hammer sensitivity tests gave some surprising results, which showed that pellets pressed from xerogel molding powders prepared by the powder/particle addition method have significantly lower sensitivities than current state-of-the-art powder mixing technology.

10 Desensitized materials are only an improvement in technology if they are still able to be ignited with reasonable power outputs. The shock initiation experiment shown in Figure 6 demonstrated this possibility when an 80 wt.% RDX xerogel molding powder pressed into a detonator pellet was able to be ignited, while a 33 wt.% RDX concentration would not ignite.
15 While RDX and PETN have been utilized in the experimental test other energetic materials such as HMX, CL-20, TNT, and peroxides may be used as ingredients.

It has thus been shown that the present invention enables the manufacture of energetic materials using sol-gel chemistry. Also, it has been
20 shown that various methods utilizing sol-gel processing successfully produce energetic materials. Also, it has been shown that sol-gel processing of energetic materials has produced desensitized detonator explosives which are still capable of initiation.

25 While specific processing procedures, materials, parameters, etc. have been described and/or illustrated to exemplify and teach the principles of the invention, such are not intended to be limiting. Modifications and

changes may become apparent to those skilled in the art, and it is intended that the invention be limited only by the scope of the appended claims.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228